CL-331-BR			
Product Specification Sheet			
HOHEING:	Calid brace fixture avenueded		
HOUSING:	Solid brass fixture, suspended inside a reversible flat or angled cut PVC sleeve, provides inground support. Fixture is adjustable inside the PVC sleeve for light aiming.		LE D AVAILABLE
FINISH:	<b>BR</b> -Natural Brass fixture. PVC sleeve available in black only.		
LENS:	Clear, tempered and heat resistant glass with a silicone gasket.		<del>- %</del> "
	See accessories & parts for special effect lenses, honeycomb louver and frosted glass lens CX-380-FR.	CL-331-BR	CX-854 DIRECT BURIAL WIRENUT AVAILABLE
LAMP TVDE	40\/ MD 40 halanaa 50\/		
LAMP TYPE:	12V, MR-16 halogen, 50W max.  See lamp guide for LED and color MR-16 lamps.	6½" \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \	
MOUNTING:	In-ground direct burial or concrete encasement. Use gravel for proper drainage. Angle cut end required to be installed 3" above the ground.	31/4"	CORONA
WIRING:	Fixture is prewired with a 3-foot pigtail of direct burial cable.	8"  -51/2"	Tel: 800-727-9262 213-747-4500 Fax: 800-727-9957 213-747-3234

- Fixture is supplied with 20W MR-16 lamp.
  Remote 12 Volt transformer is required.
  See transformers and accessories for variety of options and choices.