CL-332-BR			
Product Specification Sheet			
HOUSING:	Solid brass fixture, suspended inside a reversible flat or angled cut PVC sleeve, provides inground support. Fixture is adjustable inside the PVC sleeve for light aiming.		LED
FINISH:	BR -Natural Brass fixture. PVC sleeve available in black only.		
LENS:	Clear, tempered and heat resistant glass with a silicone gasket.		
	See accessories & parts for special effect lenses, honeycomb louver and frosted glass lens CX-380-FR.	CL-332-BR	CX-854 DIRECT BURIAL WIRENUT AVAILABLE
LAMP TYPE:	12V, MR-16 halogen, 50W max. See lamp guide for LED and color MR-16 lamps.	7 ¹ / ₄ "	
MOUNTING:	In-ground direct burial or concrete encasement. Use gravel for proper drainage. Angle cut end required to be installed 3" above the ground.	31/4"	CORONA
WIRING:	Fixture is prewired with a 3-foot pigtail of direct burial cable.	8" -51/2"	Tel: 800-727-9262 213-747-4500 Fax: 800-727-9957 213-747-3234

- Fixture is supplied with 20W MR-16 lamp.
 Remote 12 Volt transformer is required.
 See transformers and accessories for variety of options and choices.