







| | | | |
|------------------------------------|---|---|---|
| CL-333-BR | |  <p style="text-align: center;">CL-333-BR</p> |  <p style="text-align: center;">LED AVAILABLE</p> |
| Product Specification Sheet | | | |
| HOUSING: | Solid brass fixture, suspended inside a reversible flat or angled cut PVC sleeve, provides in-ground support. Fixture is adjustable inside the PVC sleeve for light aiming. | | |
| FINISH: | BR -Natural Brass fixture. PVC sleeve available in black only. | | |
| LENS: | Clear, tempered and heat resistant glass with a silicone gasket. See accessories & parts for special effect lenses, honeycomb louver and frosted glass lens CX-380-FR. | | |
| LAMP TYPE: | 12V, MR-16 halogen, 50W max. See lamp guide for LED and color MR-16 lamps. |  <p style="text-align: center;">CX-854 DIRECT BURIAL WIRENUT AVAILABLE</p> | |
| MOUNTING: | In-ground direct burial or concrete encasement. Use gravel for proper drainage. Angle cut end required to be installed 3" above the ground. | | |
| WIRING: | Fixture is prewired with a 3-foot pigtail of direct burial cable. | | |
| | | |  |
| | | |  |
| | |  <p style="text-align: center;">CORONA Lighting</p> <p style="text-align: center;">WWW.CORONALIGHTING.COM</p> <p style="text-align: center;">Tel: 800-727-9262 213-747-4500</p> <p style="text-align: center;">Fax: 800-727-9957 213-747-3234</p> | |

- Fixture is supplied with 20W MR-16 lamp.
- Remote 12 Volt transformer is required.
- See transformers and accessories for variety of options and choices.