

(800) 727-9262

(800) 727-9957 (213) 747-3234



ARCHITECTURAL GRADE SERIES

SPECIFICATION SHEET

E-Mail: sales@coronalighting.com

PRODUCT #: CL-339-BK

Fixture Specifications:

Housing: Injected molded composite for high UV stability.

Face Plate: Injected molded composite, fitted to housing with

silicone "O" ring gasket.

Finish: BK- Black, polyester powder coated finish.

Lens: Clear and heat resistant glass.

Socket: Top grade adjustable ceramic bi-pin socket with

retention clip and teflon-jacketed wire lead.

Lamp: 12V, MR-16 halogen, 50W max. L-BAB-C20 (20w)

standard. See below for available LED lamps.

Gasket: Silicone "0" ring seals faceplate to housing

providing weather tight protection.

•Well Lights

Wiring: Fixture is prewired with a 3-ft 18-2 SJT-W direct

Composite

burial cord. Wire connector available seperately.

Gel filled wire nut CX-854 may be ordered to

Corona Lighting.

Mounting: In-ground direct burial or concrete encasement.

Electrical Notes: A remote 12V transformer required, may be

ordered to Corona Lighting seperately. Voltage range for 12V halogen lamps are 11V-12.5V. Voltage range for LED lamps are 9V-17V.


Warranty: Limited ten (10) years warranty on fixture against

manufacturer's defects.





Fixture socket tilts for ± 25°





3.5W, 5W and 7W

AVAILABLE LED LAMPS							JOB INFORMATION	
LAMP NUMBER	WATTS	BRAND	BEAM SPREAD I	UMEN	COLOR & TEMP.	ORDER CODE	TYPE:	DATE:
L-EDMR16-EP-3W-FL L-EDMR16-EP-5W-FL	3.5 5	EPISTAR EPISTAR	45° Flood 45° Flood	210 270	WW 2700K WW 2700K	MR16-EP-3W-FL MR16-EP-5W-FL	JOB NAME & ADDRESS:	DAIL.
L-EDMR16-3W-WW-SP L-EDMR16-3W-WW-FL	3.5 3.5	CREE CREE	15° Spot 45° Flood	210 210	WW 2700K WW 2700K	MR16-3W-WW-SP MR16-3W-WW-FL	PRODUCT #:	
L-EDMR16-3W-WW-WF		CREE	60° Wide Flood		WW 2700K	MR16-3W-WW-WF	TOTAL QUANTITY:	
L-EDMR16-5W-WW-SP L-EDMR16-5W-WW-FL	5 5	CREE CREE	15° Spot 45° Flood	270 270	WW 2700K WW 2700K	MR16-5W-WW-SP MR16-5W-WW-FL	LAMP TYPE & WATTAGE:	
L-EDMR16-5W-WW-WF L-EDMR16-7W-WW-SP	5 7	CREE	60° Wide Flood		WW 2700K WW 2700K	MR16-5W-WW-WF	TRANSFORMER:	
L-EDMR16-7W-WW-FL	7	CREE CREE	15° Spot 45° Flood	430 430	WW 2700K	MR16-7W-WW-FL	CONTRACTOR:	
L-EDMR16-7W-WW-WF	7	CREE	60° Wide Flood	430	WW 2700K	MR16-7W-WW-WF	SPECIFIER:	