

SPECIFICATION SHEET

Los Angeles, CA 90021 TEL. FAX. (800) 727-9262 (800) 727-9957 (213) 747-4500 (213) 747-3234

1633 Staunton Ave

E-Mail: sales@coronalighting.com

| PROD | | | | | | | tep Lights | E-Mail: sales@coronalighting.co Composite |
|---|--|-----------|-----------------|-----------------------|------------|------------------|---|--|
| Fixture | _ | | _ | | | -3 | tep Lights | • Composite |
| | - | | | | | | | |
| Housing: Injected molded composite for high UV stability. Face Plate: Injected molded composite, fitted to housing with silicone "O" ring gasket. | | | | | | | ring: | Fixture is prewired with a 3-ft 18-2 SJT-W direct burial cord. Wire connector available seperately. Gel filled wire nut CX-854 may be ordered to Corona Lighting. |
| Finish : | | | | er coated finish. | | Мо | ounting: | In-ground direct burial or concrete encasement. |
| _ens: | Frosted an | id heat i | resistant gla | ISS. | | | - | A remote 12V transformer required, may be |
| Socket: Top grade adjustable ceramic bi-pin socket with retention clip and teflon-jacketed wire lead. Lamp: 12V, MR-16 halogen, 50W max. L-BAB-C20 (20w) standard. See below for available LED lamps. | | | | | | | | ordered to Corona Lighting seperately. Voltage range for 12V halogen lamps are 11V-12.5V. |
| | | | | | | | Voltage range for LED lamps are 9V-17V. | |
| Gasket: | Silicone "O" ring seals faceplate to housing providing weather tight protection. | | | | | vva | Warranty: | Limited ten (10) years warranty on fixture against manufacturer's defects. |
| | | | | | | | | |
| | | 9 | | Q | 3.5 | | | $\begin{array}{c} \hline \\ \hline $ |
| AVAILABLE LED LAMPS | | | | | | | | JOB INFORMATION |
| LAMP NUI | MBER | WATTS | BRAND | BEAN SPREAD L | UMEN | COLOR & TEMP. | ORDER CODE | |
| -EDMR16-E -EDMR16-E | P-3W-FL | 3.5 5 | EPISTAR | 45° Flood | 210 270 | WW 2700K | MR16-EP-3W-FL MR16-EP-5W-FL | TYPE: DATE: JOB NAME & ADDRESS: |
| -EDMR16-3 | | 3.5 | EPISTAR CREE | 45° Flood 15° Spot | 210 | | MR16-3W-WW-SF | _ |
| -EDMR16-3 | | 3.5 | CREE | 45° Flood | 210 | | MR16-3W-WW-FL | |
| -EDMR16-3 | W-WW-WF | 3.5 | CREE | 60° Wide Flood | 210 | WW 2700K | MR16-3W-WW-W | |
| EDMR16-5 | W-WW-SP | 5 | CREE | 15° Spot | 270 | WW 2700K | MR16-5W-WW-SF | |
| -EDMR16-5 | | 5 | CREE | 45° Flood | 270 | | MR16-5W-WW-FL | |
| EDMR16-5 | W-WW-WF | 5 | CREE | 60° Wide Flood | 270 | WW 2700K | MR16-5W-WW-W | TRANSFORMER: |
| EDMR16-7 | | 7 | CREE | 15° Spot | 430 | | MR16-7W-WW-SF | I CONTRACTOR: |
| -EDMR16-7 | | 7 | CREE | 45° Flood | 430 | | MR16-7W-WW-FL | - |
| EDMR16-7 | vv-vvvv-vvF | 7 | CREE | 60° Wide Flood | 430 | WW 2700K | MR16-7W-WW-W | F SPECIFIER: |

• Corona Lighting reserves the right to make any change and/or improvement to the design and construction of this fixure without further notification.