

(800) 727-9262

(800) 727-9957

(213) 747-3234 (213) 747-4500

E-Mail: sales@coronalighting.com



Finish:

ARCHITECTURAL GRADE SERIES

## SPECIFICATION SHEET

Step Lights

## **Fixture Specifications:**

PRODUCT #: CL-377-BK

Housing: Injected molded composite for high UV stability. Face Plate: Injected molded composite, fitted to housing with

silicone "O" ring gasket.

BK-Black, Polyester powder coated finish

Lens: Frosted and heat resistant glass.

Socket: Top grade adjustable ceramic bi-pin socket with

retention clip and teflon-jacketed wire lead.

Lamp: 12V, MR-16 halogen, 50W max. L-BAB-C20 (20w) standard. See below for available LED lamps.

Gasket: Silicone "O" ring seals faceplate to housing

providing weather tight protection.

Composite

Wiring: Fixture is prewired with a 3-ft 18-2 SJT-W direct

burial cord. Wire connector available seperately.

Gel filled wire nut CX-854 may be ordered to

Corona Lighting.

Mounting: In-ground direct burial or concrete encasement.

Electrical Notes: A remote 12V transformer required, may be

ordered to Corona Lighting seperately. Voltage range for 12V halogen lamps are 11V-12.5V. Voltage range for LED lamps are 9V-17V.


Warranty: Limited ten (10) years warranty on fixture against


manufacturer's defects.





Fixture socket tilts for ± 25°







3.5W, 5W and 7W

AVAILABLE LED LAMPS						
LAMP NUMBER	WATTS	BRAND	BEAM SPREAD LUMEN		COLOR & TEMP.	ORDER CODE
EAMI NOMBER		DIVAILE	OFFICEAD	LOWILIA	1 <b>- 14</b> 11 .	OODL
L-EDMR16-EP-3W-FL	3.5	<b>EPISTAR</b>	45° Flood	210	WW 2700K	MR16-EP-3W-FL
L-EDMR16-EP-5W-FL	5	<b>EPISTAR</b>	45° Flood	270	WW 2700K	MR16-EP-5W-FL
L-EDMR16-3W-WW-SP	3.5	CREE	15° Spot	210	WW 2700K	MR16-3W-WW-SP
L-EDMR16-3W-WW-FL	3.5	CREE	45° Flood	210	WW 2700K	MR16-3W-WW-FL
L-EDMR16-3W-WW-WF	3.5	CREE	60° Wide Flood	210	WW 2700K	MR16-3W-WW-WF
L-EDMR16-5W-WW-SP	5	CREE	15° Spot	270	WW 2700K	MR16-5W-WW-SP
L-EDMR16-5W-WW-FL	5	CREE	45° Flood	270	WW 2700K	MR16-5W-WW-FL
L-EDMR16-5W-WW-WF	5	CREE	60° Wide Flood	270	WW 2700K	MR16-5W-WW-WF
L-EDMR16-7W-WW-SP	7	CREE	15° Spot	430	WW 2700K	MR16-7W-WW-SP
L-EDMR16-7W-WW-FL	7	CREE	45° Flood	430	WW 2700K	MR16-7W-WW-FL
L-EDMR16-7W-WW-WF	7	CREE	60° Wide Flood	l 430	WW 2700K	MR16-7W-WW-WF

## JOB INFORMATION

TYPE: DATE:

JOB NAME & ADDRESS:

PRODUCT #:

TOTAL QUANTITY:

LAMP TYPE & WATTAGE:

TRANSFORMER:

CONTRACTOR:

SPECIFIER: