CL-603			
Product Specification Sheet			XENON
HOUSING:	Interlocking die-cast aluminum sections, assembled with 3 stainless steel screws.		
FINISH:	Polyester UV powder coated, available in BK -Black, GR -Green, VG -Verde Green.		AVAILABLE
LENS:	Frosted tempered glass with silicone gasket. Clear glass lens available.	CL-603	CX-839 CORONA UNIVERSAL CONNECTOR AVAILABLE
LAMP TYPE:	12V, T3/T4 halogen, 50W max.		CONNECTOR AVAILABLE
	See lamp guide for T3 xenon lamps.	←6"→	
MOUNTING:	6" cast aluminum stem with 1/2" NPT on bottom, including ground spike.	121/4" 7"	
	See accessories & parts for optional mounting hardware. When ordering with 3" post top or pier mount base add "-PT" or "-PM" to the end of the product number respectively.	6"	Tel: 800-727-9262 213-747-4500
WIRING:	Fixture is prewired with a 3-foot pigtail of direct burial cable.	<u>↓</u>	Fax: 800-727-9957 213-747-3234

- Fixture is supplied with 20W T3 halogen lamp.
- Remote 12 Volt transformer is required.
- See transformers and accessories for variety of options and choices.
- When ordering, add the 2 letter color code to the end of the product number.