MATERIAL / FEATURES

- 304 Stainless Steel Case
- ETL Approved to UL2108
- Bottom Panel pre-punched with conduit knockouts, and swings down for ease of installation and is fully removable
- Quick Mount Bracket Allows for mounting without templates
- Lifetime Warranty
- Sealed removable, lockable hinged doors

FINISH

Muted Stainless Steel

ELECTRICAL

- 6' Heavy Duty Power Cord
- Large terminal blocks allow for 10 #12/2 or 8 #10/2 wire
- Primary Side Thermal Protection
- Secondary Side Magnetic Circuit Breakers
- Fully Encapsulated Toroid Core
- Surge Suppressor provides protection against initial start overload on primary circuits
- Internal wiring rated to 125°C
- 115 AMP rated terminal block
- Primary AMP loop provided on 900 & 1200 watt models

DIMENSIONS

300, 600 watt - 6 1/5"W x 16 1/2"H x 6"D
900 watt - 8 1/2"W x 17 1/2"H x 7"D

MODELS

• MTP0300SS	300w	12,13,14,15,16,17,18,22v	Toroid Core
• MTP0600SS	600w	12,13,14,15,16,17,18,22v	Toroid Core
 MTP0900SS 	900w	12.13.14.15.16.17.18.20.22v	Toroid Core

APPLICATIONS

- LED Lighting Systems
- Water Feature Lighting
- Ideal for All Low Voltage Landscape Lighting Products



MTP1200SS





P: (888) 866-4765