

# Transformers

STL

## MATERIAL / FEATURES

- 304 Stainless Steel Case
- Quick Mount Bracket Allows for mounting without templates
- Lifetime Warranty - Stainless Steel Case and EI Core
- 1 Year Warranty - Replaceable Timer Module
- Replaceable Timer Module (Off, On, Auto, 1,2,4,6,8 Hours Off)
- Photocell (STL-PC) w/25' lead included to use Auto &
- Timed functions (for use with STL series transformers only - Low Voltage)
- ETL approved to UL1838

## FINISH

- Muted Stainless Steel

## ELECTRICAL

- 6' Heavy Duty Power Cord
- Terminals for Output and Photocell In
- Primary Side Thermal Protection
- Secondary Side Magnetic Circuit Breaker
- Fully Encapsulated EI Magnetic Core
- Internal wiring rated to 125°C

## DIMENSIONS

- 4" W x 7" H x 3.25" D

## MODELS

- |            |      |            |                  |
|------------|------|------------|------------------|
| • STL040SS | 40w  | 12/13 volt | EI Magnetic Core |
| • STL070SS | 70w  | 12/13 volt | EI Magnetic Core |
| • STL150SS | 150w | 12/15 volt | EI Magnetic Core |

## APPLICATIONS

- LED Lighting Systems
- Water Feature Lighting
- Small Landscape Lighting Projects



STL070SS



**U-Sync** READY

