

### LANDSCAPE LIGHTING



_

#### **PRODUCT DESCRIPTION**

Landscape accent luminaire. One fixture replaces all older halogen landscape accent lights

#### **FEATURES**

- Adjustable and lockable beam angle
- Integral dimmer
- IP66 rated, Protected against high-pressure water jets
- Includes a detachable shroud
- Solid diecast brass or corrosion resistant aluminum
- Factory sealed water tight fixtures
- Mounting stake, 6' lead wire and direct burial gel filled wire nuts included
- Maintains constant lumen output against voltage drop
- UL 1838 Listed
- Not suitable to use with external dimmers

#### **ORDERING NUMBER**

		Color Temp		Finish	
5011	Accent 12V	27 30	2700K 3000K	BK BZ BBR	Black on Aluminum Bronze on Aluminum Bronze on Brass

5011-

Example: 5011-30BBR

#### **SPECIFICATIONS**

**Input:** 9 - 15VAC (Transformer is required)

**Power:** 2W to 16W / 2VA - 23VA **Brightness:** 190 lm to 1045 lm

Beam Angle: 10° to 60°

Rated Life: 70,000 hours

# **ACCENT 12V**

# 5011



Accessories			
Accent Snoot	5010-SNOOT-BK 5010-SNOOT-BZ 5010-SNOOT-BBR	Black on Aluminum Bronze on Aluminum Bronze on Brass	Shields lamp and reduces glare
6" Long Shroud	5010-LSHR-BK 5010-LSHR-BZ 5010-LSHR-BBR	Black on Aluminum Bronze on Aluminum Bronze on Brass	Reduce glare. Ideal for downlighting application
Additional Stake	9000-ST9-BZ	Bronze	Durable PVC stake
Surface Mount Flange/Stake	5000-SCP-BZ 5000-SCP-BBR 5000-SCP-BK	Bronze on Aluminum Bronze on Brass Black on Aluminum	Includes three 7 inch threaded stainless steel stabilizing pins for ground mounting or surface mounts with four screws or over a junction box
Guardian Mount	9000-SP9-BZ	Stainless Steel	Heavy duty stainless steel spike to position fixture Formed from a single piece of metal
Gutter Mount Bracket	5000-GM-BK	Stainless Steel	Stainless Steel universal mounting bracket for gutter mounting fixture
Tree Mount Junction Box	5000-TCP-BZ 5000-TCP-BK	Bronze on Aluminum Black on Aluminum	Bronze on Aluminum box with Stainless steel mounting screws. Two $\frac{1}{2}$ " NPT threaded holes
Optics	LENS-20-AMB Amber LENS-20-GRN Green LENS-20-RED Red	LENS-20-BLU Blue LENS-20-FR Frosted LENS-20-SPR Spread	Enhances saturation of florals and foliage
Extension Rods	5000-X04-BZ 4 in 5000-X04-BK 4 in 5000-X08-BZ 8 in 5000-X08-BK 8 in 5000-X12-BZ 12 in 5000-X12-BK 12 in	5000-X18-BZ 18 in 5000-X18-BK 18 in 5000-X24-BZ 24 in 5000-X24-BK 24 in	Extends distance between Accent light and Surface Mount Canopy, Stake, or Tree Mount box
Rod L-Coupler	5000-LCO-BZ	Bronze	

### **Magnetic Transformers**

Stainless Steel, 12-15V output, IP65 rated, UL 1838 listed See transformer spec sheet for details and its accessories

**9075-TRN-SS** *75W Max* 

**9150-TRN-SS** *150W Max* 

**9300-TRN-SS** *300W Max* 

**9600-TRN-SS** 600W Max

