

2" INGROUND - ROUND

2022 Honeycomb louver

WAC

LANDSCAPE LIGHTING



Fixture Type:

Catalog Number:

Project: _____

Location: _____

PRODUCT DESCRIPTION


Landscape 2" recessed in-ground luminaire for up, down, side light applications.

FEATURES

- Integrated honeycomb louver for reduced glare
- 30° visual cutoff
- IP68 rated, Suitable for continuous immersion under water
- Factory sealed water tight fixtures
- Solid stainless steel construction
- Stainless steel spring clip allows wall or downlight applications
- Available Concrete Pour Adapter
- Spring, and 6' lead wire and direct burial gel filled wire nuts included
- Maintains constant lumen output against voltage drop
- UL 1838 Listed

SPECIFICATIONS

Input: 9 - 15VAC (Transformer is required)
Power: 4.1W / 6.6VA
Brightness: 170 lm
Beam Angle: 25°
CRI: 85
Rated Life: 70,000 hours



ORDERING NUMBER

| | | Color Temp | | Finish | |
|-------------|-----------------------------------|------------|-------|-----------|--------------------------------|
| 2022 | <i>Round Honeycomb Louver</i> | 27 | 2700K | BS | <i>Bronzed Stainless Steel</i> |
| | | 30 | 3000K | SS | <i>Stainless Steel</i> |

| IEC safety Standard | Walk over | Drive over |
|---|--------------------------------|---------------|
| | Resistance to static load test | Yes (1125lbs) |
| Resistance to torque and shear loads test | N/A | Yes |

2022-30 _____

Example: **2022-30SS**

wacighting.com
 Phone (800) 526.2588
 Fax (800) 526.2585

Headquarters/Eastern Distribution Center
 44 Harbor Park Drive
 Port Washington, NY 11050

Central Distribution Center
 1600 Distribution Ct
 Lithia Springs, GA 30122

Western Distribution Center
 1750 Archibald Avenue
 Ontario, CA 91760

2" INGROUND - ROUND

2022 Honeycomb louver

WAC

LANDSCAPE LIGHTING

Magnetic Transformers



Stainless Steel, 12-15V output,
IP65 rated, UL 1838 listed
See transformer spec sheet for
details and its accessories


9075-TRN-SS
75W Max

9150-TRN-SS
150W Max

9300-TRN-SS
300W Max

9600-TRN-SS
600W Max

2" Concrete Pour Kit



For installation in concrete.
Use with a 4" outdoor rated junction box
and a trade size 2" schedule 80 PVC pipe

2000-CON-PVC

TESTED MAGNETIC LOW VOLTAGE (MLV) DIMMERS

| Luminaire | Dimmer | | | | | |
|-------------|--------------|---------|----------|--------------|------------|------------------|
| | Manufacturer | Family | Model | Power Rating | Range* | Note |
| 2022 | Lutron | Diva | DVLV-600 | 600W | 20% - 100% | |
| | | Skylark | SLV-600P | 600W | 15% - 100% | Best performance |
| | | Skylark | S-10P | 1000W | | Not recommended |

*Low end of this range is determined by output current which may not directly translate to the perceived light output

WAC Lighting fixtures are compatible with a variety of dimmers. For your convenience we have included a compatibility chart showing dimmers which have been tested with our products. The recommended list below is based upon testing conducted in a lab, and the results can vary in certain field applications due to a number of factors. Exclusion from the list does not imply incompatibility, just that it has not been tested by WAC Lighting. Please reference the dimmer manufacturer's instructions for installation, or contact a WAC lighting professional at 800-526-2588.

waclighting.com
Phone (800) 526.2588
Fax (800) 526.2585

Headquarters/Eastern Distribution Center
44 Harbor Park Drive
Port Washington, NY 11050

Central Distribution Center
1600 Distribution Ct
Lithia Springs, GA 30122

Western Distribution Center
1750 Archibald Avenue
Ontario, CA 91760