



LANDSCAPE LIGHTING







Location:



PRODUCT DESCRIPTION

Landscape 2" recessed inground luminaire washes walkways with a shadow-free smooth llumination.

FEATURES

- Factory sealed water tight fixtures
- Cold Weather Start: -40^oC to 50^oC
- Solid stainless steel construction
- Available Concrete Pour Adapter
- Spring clip, 6' lead wire and direct burial gel filled wire nuts included

SPECIFICATIONS

Input: 9 - 15VAC (Transformer is required)

 Power:
 4.1W / 6.6VA

 Brightness:
 5 lm

 CRI:
 85

Rated Life: 70,000 hours

ORDERING NUMBER

	Color Temp	Finish		
2071	27 2700K 30 3000K	BS Bronzed Stainless Steel SS Stainless Steel		

IEC safety Standard	Walk over	Drive over
Resistance to static load test	Yes (1125lbs)	Yes (4496lbs)
Resistance to torque and shear loads test	N/A	Yes

2071-30

Example: 2071-30SS

2" INGROUND

2071



Magnetic Transformers



Stainless Steel, 12-15V output, IP65 rated, UL 1838 listed See transformer spec sheet for details and its accessories

9075-TRN-SS 75W Max

9150-TRN-SS 150W Max

9300-TRN-SS 300W Max

9600-TRN-SS 600W Max

2" Concrete Pour Kit





For installation in concrete. Use with a 4" outdoor rated junction box and a trade size 2" schedule 80 PVC pipe

2000-CON-PVC

TESTED MAGNETIC LOW VOLTAGE(MLV) DIMMERS

Luminaire	Dimmer					
Luminaire	Manufacturer	Family	Model	Power Rating	Range*	Note
		Diva	DVLV-600	600W	20% - 100%	
2071	Lutron	Skylark	SLV-600P	600W	15% - 100%	Best performance
		Skylark	S-10P	1000W		Not recommended

^{*}Low end of this range is determined by output current which may not directly translate to the perceived light output

WAC Lighting fixtures are compatible with a variety of dimmers. For your convenience we have included a compatibility chart showing dimmers which have been tested with our products. The recommended list below is based upon testing conducted in a lab, and the results can vary in certain field applications due to a number of factors. Exclusion from the list does not imply incompatibility, just that it has not been tested by WAC Lighting. Please reference the dimmer manufacturer's instructions for installation, or contact a WAC lighting professional at 800-526-2588.