

2216 Aluminum | 50 W max (halogen) | MR-16 Lamp or LED | LN-20 BAB Std



2416 Composite | 20 W max (halogen) | MR-16 Lamp or LED | LN-20 BAB Std



| | | | | |
|------|---------------------------|---|---------------------|---|
| 2216 | HOUSING/SHROUD | <ul style="list-style-type: none"> » Die-cast » Copper-free aluminum » Silicone O-ring gasket » Superior weather-tight seal | LAMP TYPE | <ul style="list-style-type: none"> » Standard lamp included with fixture. For other lamp and wattage options see Lamp Guide, pages 128-130. |
| | FINISH | <ul style="list-style-type: none"> » Polyester powder-coated finish. See ordering information for available colors. | PHOTOMETRICS | <ul style="list-style-type: none"> » For photometric data, see pages 131-149. |
| 2416 | SOCKET/LAMP HOLDER | <ul style="list-style-type: none"> » Proprietary ceramic socket » Nickel contacts » Stainless steel springs » Teflon-jacketed wire leads | MOUNTING | <ul style="list-style-type: none"> » Adjustable knuckle with 1/2" NPT » Injection-molded, reinforced polymer » Fixture may be mounted into threaded hubs in junction boxes, ground stakes, tree mount boxes, or mounting canopies. » See ordering information for mounting options. For optional mounting accessories, see pages 126-127. |
| | LENS | <ul style="list-style-type: none"> » Clear » Tempered » Shock- and heat-resistant » Soda-lime glass » For optical effect lenses, see ordering information. | FASTENERS | <ul style="list-style-type: none"> » Stainless steel fasteners |
| | | | WIRING | <ul style="list-style-type: none"> » Prewired with a three-foot pigtail of 18-2 direct-burial cable and underground connectors for a secure connection to the supply cable. |

LED SPECIFICATIONS Look for this mark on products where LED options are available.

LED Lamp
 High Output Plug-in LED lamp with Vista exclusive smart-driver, powered to operate for 30,000 hours with an operating voltage of 9-15 VAC. See page 128 for extended specifications and options.

ORDERING INFORMATION Select appropriate choice from each column **example: GR-2216-B-BAB-HL**

| Mounting | No. | Finish | Lamp | Lenses/Accessories |
|----------------------------|------|-------------------------|------------------------------------|-------------------------|
| GR Ground stake | 2216 | B Black | See reference codes, pages 128-130 | BL Flat Cool Blue Lens |
| WR Wall mount canopy | 2416 | Z Architectural Bronze* | | SL Flat Spread Lens |
| TR Tree-mount junction box | | DZ Dark Bronze | | FR Flat Frosted Lens |
| | | LZ Light Bronze | | CX Convex Clear Lens |
| | | SB Special Bronze | | CFR Convex Frosted Lens |
| | | G Verde | | DBL Flat Dark Blue Lens |
| | | P Pewter | | GL Flat Dark Green Lens |
| | | BR Architectural Brick | | RL Flat Red Lens |
| | | GT Granite | | YL Flat Amber Lens |
| | | TC Terracotta | | HL Honeycomb Louver |
| | | R Rust | | |
| | | HG Hunter Green | | |
| | | M Mocha | | |
| | | WB Weathered Bronze | | |
| | | WI Weathered Iron | | |
| | | W White | | |

NOTE: not all accessories are available for all fixtures. See footnotes below before ordering.
 * Not available for fixtures with composite polymer housings.
 Fixtures shipped with standard lamp, unless otherwise specified, and with specified mounting hardware.