
16 12-VOLT SERIES | UP & ACCENT LIGHTS



HOUSING/SHROUD

- » Die-cast
- » Copper-free aluminum
- » Silicone O-ring gasket
- » Superior weather-tight seal

EINIICH

» Polyester powder-coated finish. See ordering information for available colors.

LED

- » High output emitters
- » Powered to operated for 50,000 hours
- » Vista exclusive smart driver
- » Suitable for dimming

OPTICS

- » Mirror finish aluminum reflector
- » Available in narrow spot through wide flood beam spreads

LENS

- » Clear
- » Tempered
- » Shock- and heat-resistant
- » Soda-lime glass
- » For optical effect lenses, see ordering information.

ELECTRICAL

- » Input voltage range 9-15 VAC
- » Regulated for uniform illumination throughout the cable run of fixtures
- » Allows for mixing with other halogen fixtures on existing wiring

PHOTOMETRICS

» For photometric data, see pages 131-149.

MOUNTING

- » Adjustable knuckle with ½" NPT
- » Injection-molded, reinforced polymer
- » Fixture may be mounted into threaded hubs in junction boxes, ground stakes, tree mount boxes, or mounting canopies.
- » See ordering information for mounting options. For optional mounting accessories, see pages 126-127.

FASTENERS

» Stainless steel fasteners

WIRING

» Prewired with a three-foot pigtail of 18-2 direct-burial cable and underground connectors for a secure connection to the supply cable.

