



**PROFESSIONAL  
OUTDOOR LIGHTING**

Type:

Model:

Project:

# SPECIFICATION SHEET

## MODEL 5013i Landscape Series • Up & Accent Lights

### FIXTURE SPECIFICATIONS:

**HOUSING:**

Die-cast, copper-free aluminum.

**SHROUD:**

Die-cast, copper-free aluminum fitted to housing with a silicone O-ring gaskets – providing a superior weather-tight seal.

**FINISH:**

Polyester powder-coat finish available in Black, Verde, Architectural Brick, Architectural Bronze, Light Bronze, Dark Bronze, Special Bronze, Granite, Pewter, Graphite Metallic, Rust, Hunter Green, Mocha, Weathered Bronze, Weathered Iron, and White.

**LENS:**

Clear, tempered, shock and heat-resistant, soda-lime glass lens.

**LAMP TYPE:**

COB Array driven at 1.5 watts - 2.5W or 3.5W . Color temperature available in W-Warm (3000K), N-Neutral (4000K), C-Cool (5000K).

**ELECTRICAL:**

Input voltage range 9-15V AC regulated to achieve uniform illumination throughout the cable run of fixtures. Integral surge & reverse polarity protection

**OPTICS:**

Available in 25° Spot, 36° Medium Flood and 60° Wide Flood.

**MOUNTING:**

Injection-molded composite adjustable knuckle with 1/2" NPS thread. Fixture may be mounted into threaded hubs in junction boxes, ground stakes (GR), tree mount boxes (TR), or mounting canopies (WR).

**FASTENERS:**


All fasteners are stainless steel.

**WIRING:**

Prewired with a 36" pigtail of 18-2 direct-burial cable and underground connectors for a secure connection to supply cable.

All Vista luminaires are **MADE IN U.S.A.**

### DIMENSIONS:



*Vista Professional Outdoor Lighting reserves the right to modify the design and/or construction of the fixture shown without further notification.*



# SPECIFICATION SHEET

## MODEL 5013i Landscape Series • Up & Accent Lights

### FIXTURE ORDERING INFORMATION

TO ORDER FIXTURE: Select appropriate choice from each column as in the following example.

**EXAMPLE: GR-5013i-B-2-W-SP-FR**

MOUNTING	MODEL	FINISH	WATTAGE	COLOR TEMP	DISTRIBUTION	ACCESSORIES
GR- ABS ground stake WR- Wall-mount canopy TR- Tree-mount junction box	5013i	Standard	1.5	W - Warm	SP- 25° Spot	FR - Frosted Lens
		B - Black	2.5	N - Neutral	MF - 36° Flood	
		Z - Architectural Bronze	3.5	C - Cool	WF - 60° Wide	
		DZ - Dark Bronze				
		W - White				
		Premium				
		BR - Architectural Brick				
		LZ - Light Bronze				
		SB - Special Bronze				
		GT - Granite				
		R - Rust				
		HG - Hunter Green				
		WB - Weathered Bronze				
WI - Weathered Iron						
GM - Graphite Metallic						
Hand Finished						
G - Verde						
P - Pewter						
M - Mocha						

Fixtures shipped with specified mounting hardware.