

5212 Aluminum | 75 W max (halogen) | T4 Lamp or LED | LN-20 T4 Std



5103 Aluminum | 75 W max (halogen) | T4 Lamp or LED | LN-20 T4 Std



5203



5204



5104



	HOUSING/SHROUD	REFLECTOR	FINISH
5103	<ul style="list-style-type: none"> » Die-cast copper-free aluminum » Superior weather-tight seal 	<ul style="list-style-type: none"> » Aluminum » Mirror finish 	<ul style="list-style-type: none"> » Polyester powder-coated finish. See ordering information for available colors.
5104	<ul style="list-style-type: none"> » Die-cast copper-free aluminum » Superior weather-tight seal 		SOCKET/LAMP HOLDER <ul style="list-style-type: none"> » Proprietary ceramic socket » Nickel contacts » Stainless steel springs » Teflon-jacketed wire leads
5203	<ul style="list-style-type: none"> » Injection-molded, reinforced polymer » Formulated for most Vista polyester powder-coated finishes » Exceptional strength and UV stability » Superior weather-tight seal 	<ul style="list-style-type: none"> » Aluminum » Mirror finish 	LENS <ul style="list-style-type: none"> » Clear » Tempered » Shock- and heat-resistant » Soda-lime glass » For optical effect lenses, see ordering information.
5204	<ul style="list-style-type: none"> » Injection-molded, reinforced polymer » Formulated for most Vista polyester powder-coated finishes » Exceptional strength and UV stability » Superior weather-tight seal 		LAMP TYPE <ul style="list-style-type: none"> » Standard lamp included with fixture. For other lamp and wattage options see Lamp Guide, pages 128-130.
5212	<ul style="list-style-type: none"> » Die-cast copper-free aluminum » Superior weather-tight seal 	<ul style="list-style-type: none"> » Aluminum » Mirror finish 	PHOTOMETRICS <ul style="list-style-type: none"> » For photometric data, see pages 131-149.
			MOUNTING <ul style="list-style-type: none"> » Adjustable knuckle with 1/2" NPT » Injection-molded, reinforced polymer » Fixture may be mounted into threaded hubs in junction boxes, ground stakes, tree mount boxes, or mounting canopies. » See ordering information for mounting options. For optional mounting accessories, see pages 126-127.
			FASTENERS <ul style="list-style-type: none"> » Stainless steel fasteners
			WIRING <ul style="list-style-type: none"> » Prewired with a three-foot pigtail of 18-2 direct-burial cable and underground connectors for a secure connection to the supply cable.

LED SPECIFICATIONS Look for this mark on products where LED options are available.

LED Lamp	Integrated LED
High Output Plug-in LED lamp with Vista exclusive smart-driver, powered to operate for 30,000 hours with an operating voltage of 9-15 VAC. See page 128 for extended specifications and options.	High Output LED lamp assembly with Vista exclusive smart-driver, powered to operate for 50,000 hours with an operating voltage of 9-15 VAC. See page 130 for extended specifications and options.

ORDERING INFORMATION Select appropriate choice from each column example: GR-5103-B-20 T4-FR

Mounting	No.	Finish	Lamp	Lenses/Accessories
GR Ground stake	5103	B Black	LAMP	FR Flat Frosted Lens**
WR Wall mount canopy	5104	Z Architectural Bronze*	See reference codes, pages 128-130	HL Honeycomb Louver
TR Tree-mount junction box	5203	DZ Dark Bronze	INTEGRATED LED	
	5204	LZ Light Bronze	See reference codes, page 130, group B	
	5212	SB Special Bronze		
		G Verde		
		P Pewter		
		BR Architectural Brick		
		GT Granite		
		TC Terracotta		
		R Rust		
		HG Hunter Green		
		M Mocha		
		WB Weathered Bronze		
		WI Weathered Iron		
		W White		

NOTE: not all accessories are available for all fixtures. See footnotes below before ordering.
 * Not available for fixtures with composite polymer housings.
 ** Frosted lens standard with LED Fixtures.
 Fixtures shipped with standard lamp, unless otherwise specified, and with specified mounting hardware.