

SPECIFICATION SHEET

1633 Staunton Ave Los Angeles, CA 90021 FAX. TEL. (800) 727-9957 (800) 727-9262 (213) 747-3234 (213) 747-4500

E-Mail: sales@coronalighting.com

PRODUCT #: CL-375-BK

Fixture Specifications:

Housing:	Injected molded composite for high UV stability.
Face Plate	Injected molded composite, fitted to housing with silicone "O" ring gasket.
Finish :	BK-Black, Polyester powder coated finish.
Lens:	Frosted and heat resistant glass.
Socket:	Top grade adjustable ceramic bi-pin socket with retention clip and teflon-jacketed wire lead.
Lamp:	12V, MR-16 halogen, 50W max. L-BAB-C20 (20w) standard. See below for available LED lamps.
Gasket:	Silicone "O" ring seals faceplate to housing providing weather tight protection.

•Step Lights	Composite				
Wiring:	Fixture is prewired with a 3-ft 18-2 SJT-W direct burial cord. Wire connector available seperately. Gel filled wire nut CX-854 may be ordered to Corona Lighting.				
Mounting:	In-ground direct burial or concrete encasement.				
Electrical Notes:	A remote 12V transformer required, may be ordered to Corona Lighting seperately. Voltage range for 12V halogen lamps are 11V-12.5V. Voltage range for LED lamps are 9V-17V.				
Warranty:	Limited ten (10) years warranty on fixture against manufacturer's defects.				







Fixture socket tilts for ± 25°



3.5W, 5W and 7W





AVAILABLE LED LAMPS

AVAILABLE LED LA	MPS		JOB INFORMATION					
LAMP NUMBER	WATTS	BRAND	BEAN SPREAD L	UMEN	COLOR &	ORDER CODE		
							TYPE:	DATE:
L-EDMR16-EP-3W-FL L-EDMR16-EP-5W-FL	3.5 5	EPISTAR EPISTAR	45° Flood 45° Flood	210 270	WW 2700K WW 2700K	MR16-EP-3W-FL MR16-EP-5W-FL	JOB NAME & ADDRESS:	
L-EDMR16-3W-WW-SP	3.5	CREE	15° Spot	210	WW 2700K	MR16-3W-WW-SP		
L-EDMR16-3W-WW-FL	3.5	CREE	45° Flood	210	WW 2700K	MR16-3W-WW-FL	PRODUCT #:	
L-EDMR16-3W-WW-WF	3.5	CREE	60° Wide Flood	210	WW 2700K	MR16-3W-WW-WF	TOTAL QUANTITY:	
L-EDMR16-5W-WW-SP	5	CREE	15° Spot	270	WW 2700K	MR16-5W-WW-SP	TOTAL QUANTITY:	
L-EDMR16-5W-WW-FL	5	CREE	45° Flood	270	WW 2700K	MR16-5W-WW-FL	LAMP TYPE & WATTAGE:	
L-EDMR16-5W-WW-WF	5	CREE	60° Wide Flood	270	WW 2700K	MR16-5W-WW-WF	TRANSFORMER:	
L-EDMR16-7W-WW-SP	7	CREE	15° Spot	430	WW 2700K	MR16-7W-WW-SP		
L-EDMR16-7W-WW-FL	7	CREE	45° Flood	430	WW 2700K	MR16-7W-WW-FL	CONTRACTOR:	
L-EDMR16-7W-WW-WF	7	CREE	60° Wide Flood	430	WW 2700K	MR16-7W-WW-WF	SPECIFIER:	

• Corona Lighting reserves the right to make any change and/or improvement to the design and construction of this fixure without further notification.