



FIXTURE CONFIGURATION

NBZ

H20-402B

NBZ NATURAL BRONZE

100 100 FT LEAD OPTION

*Standard Lead is 25 FT

Leave empty if you want standard option

ALTERNATIVE INSTALL OPTION

LEAD OPTION -

PROJECT	DATE
ТҮРЕ	CATALOG #

MARINER H20-402B

KEY FEATURES


•HEAVY CAST BRASS •REMOVABLE STAND FOR LOW PROFILE INSTALL •25 FT UNDERWATER RATED SJ CABLE **•HIGH TEMPERATURE SOCKET** •FIELD REPLACEABLE LED

PRODUCT SPECIFICATION

MATERIAL	CAST BRASS
LENS	CLEAR FLAT TEMPERED
SOCKET	BI PIN
LAMP	MR11
VOLTAGE	12V AC/DC
LEAD WIRE	25 FT SJTW WIRE (18AWG INSIDE)
	(100 FT OPTIONAL)
PROJECTION	UP TO 25 FT
MAX DEPTH	UP TO 6 FT

STEP 2

LED LAMP CONFIGURATION



+ Dimmable: See MR11 LED Lamps Spec Sheet for additional details

INSTALLATION NOTE: It is important to hand tighten and seal this

3"H

STEP 1

FINISH -

USE WITHOUT MOUNTING BASE FOR LOW PROFILE **INSTALLATIONS**

fixture with silicone before placing the fixture into water. For added protection - Apply silicone around the outside of the front cap and the bottom cord exit.

Revised 08/18

LIGHTCRAFT OUTDOOR | 9811 OWENSMOUTH AVE | UNIT 1 | CHATSWORTH, CA 91311 PHONE: 818.349.2663 | FAX: 818.349.2676 | E-MAIL: SALES@LIGHTCRAFTOUTDOOR.COM