

PROJECT	DATE
TYPE	CATALOG #

$^{15}/_{16}$ "W **T** 1"H WINDOW 15"H

ILLUMA 15

AP-340B-SS-15

KEY FEATURES

- **•CONTEMPORARY DESIGN**
- **·SOLID BRASS**
- ·STAINLESS STEEL FINISH
- **•UV PROTECTED FROSTED ACRYLIC LENS**
- ·HIGH TEMPERATURE SOCKET
- ·FIELD REPLACEABLE LED

PRODUCT SPECIFICATION

LENS FROSTED ACRYLIC

SOCKET BI PIN

LAMP **ENCAPSULATED T3/G4**

9-18V AC/DC **VOLTAGE** LIGHT SPREAD 6-8 FT AVG

LEAD WIRE 3 FT

STEP 1

FIXTURE CONFIGURATION

ETL LISTED COMPLIES WITH UL1838

AP-340B-15

SS


1/2" NPT

FINISH OPTION -

SS STAINLESS STEEL

STEP 2

LED LAMP CONFIGURATION



ENC ENCAPSULATED (IP67)

STEP 3

ACCESSORY OPTIONS

AX-800P INCLUDED

STAKE OPTION -

AX-800P STANDARD SLOTTED STAKE AX-802P HEAVY DUTY PERMA POST

⁺ Dimmable: See ENCAPSULATED T3 LED Lamps Spec Sheet for additional details