

## MR16


Indoor, GU5.3 Base



### Key Features & Benefits

The 12V MR16 GU5.3 base LED series is designed for budget constraint application. Available: 7W options. This series LED light bulbs are highly versatile, which can be used from landscape lighting, deck lighting to tree post lights and offer significant energy savings, and environmentally friendly. Light output is only 36° and 60° beam.

### Technical Specifications:

|                               |  |
|-------------------------------|--|
| <b>Model Name</b>             | <b>JQ-MR16-A07K27M [CCT:2700K]-36/60(option)</b><br><b>JQ-MR16-A07K30M [CCT:3000K]-36/60(option)</b> |
| <b>Photo</b>                  |                   |
| <b>Halogen Replacement</b>    | <b>60 Watt</b>   |
| <b>Operating Voltage:</b>     | 9 ~ 15 VDC/AC  |
| <b>Power consumption:</b>     | 7 Watt   |
| <b>Dimming:</b>               | Yes  |
| <b>Dimensions:</b>            | 1.61"x1.93"D   |
| <b>CRI:</b>                   | > 85   |
| <b>CCT Option:</b>            | 2700K, 3000K   |
| <b>Luminous Flux:</b>         | 600 lumens   |
| <b>Operating Temperature:</b> | -20° C - +50° C  |
| <b>Storage Temperature:</b>   | -30° C - +60° C  |
| <b>Lens Bin Option:</b>       | 36° (Standard), 18° and 60° option   |
| <b>IP Rating</b>              | IP54   |
| <b>Safety Certification:</b>  | <b>ETL, FCC Compliance</b>   |
| <b>Rated Lifespan:</b>        | >25,000hrs.  |

**Notes** Wattage +/- 10% ; Lumen Values +/- 5Lms. CRI +/- 5% ; Dimmable\* fully tested with LUTRON© DVEL magnetic low voltage dimmer or electrical dimmer with minimum load

Distributed by Yardillumination.com

120 North Pacific Street E-1  
San Marcos, CA 92069  
866-523-7774

© Copyright 2018 JQ Green America Inc.