




CA10Flame tip E12 or E26 base



Key Features & Benefits

The new 120VE12 or medium base **CA10 (flame tip)** LED series integrates a set of filament LED sources and is ideal to replace incandescent bulbs. Available: 2W, 4W, 6W options. This series LED light bulbs are highly versatile, which can be in lanterns, fan or chandelier fixtures and offer significant energy savings and environmentally friendly. Light output is 360° which is perfect for even dispersion applications.

Technical Specifications

| Model Name | JQ-CE12-B02K27 | JQ-CE12-B04K27 JQ-CE26-B04K27 | JQ-CE12-B06K27 JQ-CE26-B06K27 |
|------------------------|--|---|--|
| Photo |  |  |  |
| Halogen Replacement | 25 Watt | 40 Watt | 50 Watt |
| Operating Voltage: | 120AC | 120 AC | 120 AC |
| Power consumption: | 2 Watt | 4 Watt | 6 Watt |
| Dimmable: * | Yes | Yes | Yes |
| Dimensions: | 3.97" x 1.19"D | 3.97" x 1.25"D | 3.97" x 1.25"D |
| CRI: | 85 | 85 | 85 |
| CCT Option: | 2700K | 2700K | 2700K |
| Luminous Flux: | 200 lm. | 360 lm. | 480 lm. |
| Operating Temperature: | -20° C- +50° C | -20° C- +50° C | -20° C- +50° C |
| Storage Temperature | -30° C- +60° C | -30° C- +60° C | -30° C- +60° C |
| Safety Certification: | FCC Compliance | ETL, FCC Compliance | FCC Compliance |
| Rated Lifespan: | >15,000hrs. | >15,000hrs. | >15,000hrs. |

Notes Wattage +/-10% ; Lumen Values +/-5Lms. CRI +/- 5% ; Dimmable* fully tested with LUTRON® DVCLDVEL etc.