

## LED – LXC MR16

## LXC2, LXC3, LXC5

## SPECIFICATIONS

- Machined Aluminum Body
- Epoxy Potted Circuitry – IP67 Rated
- GU5.3 BASE SOCKET
- 80+ CRI
- 95+ CRI14
- 40,000 Hour rated
- Multiple Beam Spreads
  - (NS) Narrow Spot 15°
  - (FL) Flood 40°
  - (WFL) Wide Flood 60°
- Stainless Steel Pins
- Made for use in Enclosed Fixtures and Damp Location
- 2700K and 3000K Color Temperature

## ELECTRICAL

- 9-15 V AC/DC
- Constant Current Driver Included for Long Life
- Dimmable with Lutron Magnetic Dimmers
  - Dimming may Reduce Life Span
- Enclosed Fixture Required (Not Included)
- Low Voltage Transformer or Electronic Transformer Required (Not Included)
- C ETL Listed and Approved
- LXC2-MR16 -27K (250 Lumens 2.5 Watts)
- LXC2-MR16 -30K (270 Lumens 2.5 Watts)
- LXC3-MR16 -27K (400 Lumens 5 Watts)
- LXC3-MR16 -30K (425 Lumens 5 Watts)
- LXC5-MR16 -27K (550 Lumens 7 Watts)
- LXC5-MR16 -30K (600 Lumens 7 Watts)

## MODELS

- LXC2-MR16-NS-27K or LXC2-MR16-NS-30K
- LXC2-MR16-FL-27K or LXC2-MR16-30K
- LXC2-MR16-WFL-27K or LXC2-MR16-WFL-30K
- LXC3-MR16-NS-27K or LXC3-MR16-NS-30K
- LXC3-MR16-FL-27K or LXC3-MR16-30K
- LXC3-MR16-WFL-27K or LXC3-MR16-WFL-30K
- LXC5-MR16-FL-27K or LXC5-MR16-30K
- LXC5-MR16-WFL-27K or LXC5-MR16-WFL-30K



LXC2



LXC3



LXC5

